

ZERO FUEL, CLEAN REPLACEMENT FOR PETROL + DIESEL GENERATORS
CLEAN ENERGY - NO POLLUTION + SILENT OPERATION



AC Charging - Available in 230V or 110V

TYPICAL USES



Construction



Flood Lighting



Garden Tools



Drones



Dehumidifiers
Heaters/Dryers



Film
Photography
Events



Household
Appliances



Microwave



Washing
Machines



Outdoor
Activities



Electrical
Devices



TV

CHARGES OPTIONS

AC CHARGER
(Supplied)

SOLAR CHARGING
(Optional)

VEHICLE CHARGING
(Optional)

INDUSTRIAL



EXTENDABLE
HANDLE

RCBO
PROTECTION



ONE MAN LIFT

ULTRA-RUGGED
CASE WITH
LIFETIME
WARRANTY

230V OR 110V
MODELS
AVAILABLE

PURE
SINEWAVE
OUTPUT

FAN
ASSISTED
COOLING

3000+
CYCLES
(APPROX 10
YEARS)

LCD
DISPLAY

IP67
WATERPROOF
CASE

WHEELS
(3000W MODEL)

OPTIONAL EXPANDABLE BATTERY PACKS

Add more power
1540Wh each



4 Hours
Charging Time

**Up to 8 Additional
CAPACITY 13860 (WH)**

Battery type
LiFePO4

No. Cycles
3000+

Weight (kg):
18 EACH

Size l x w x h (mm):
429 X 328 X 236



5 YEARS WARRANTY ★

- AC Charging
- Available in 230V or 110V



	GenZero 3000W	GenZero 1500W	GenZero 600W	
TECHNICAL SPECIFICATIONS	Continuous Output	3000W	1500W	600W
	Peak Output	6000W	3000W	1200W
	Battery Capacity (Wh)	1540Wh	922Wh	615Wh
	Battery Type	LiFePO4		
	Charging Time	4 Hours	3 Hours	2 Hours
	Ingress Protection	IP67		
	Storage/Operating Temperature	-20 To +45		
	Charge Methods	AC mains (Supplied) • Solar panel charger or Vehicle charger (Optional)		
	AC Output Voltage	Select: 110V or 230V		
	USB Outputs	1 x USB + 1 x USB-C		
	Life Of Battery	3000+ cycles		
	AC Charger Supplied	10A	10A	5A
	NET Weight	31.8kg	18.2kg	12.5kg
	Dimensions	579 x 465 x 297mm	505 x 409 x 257mm	429 x 328 mm x 236mm
Product Code	GZ-3000W-110V/230V	GZ-1500W-110V/230V	GENZERO-600W-110V/230V	

LCD DISPLAY



- Battery capacity
- Current flow
- Battery voltage
- Discharge
- Runtime at current discharge

RCBO



RCBO RESIDUAL CURRENT BREAKER + OVER CURRENT PROTECTION

BMS PROTECTION

OVERCHARGE, OVERCHARGE DISCHARGE, TEMPERATURE/SHORT-CIRCUIT